

ACE-828A



规格

输入类型	90 ~ 130VAC, 180 ~ 260VAC 自动选择范围					
输出电压	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	8A	25A (2A min)	10A (0.1A min)	0.5A	0.5A	0.72A
效率	65%					
温度	操作: -20 ~ 70°C (40 ~ 70°C 降负荷曲线) 存储: -40 ~ 75°C					
MTBF(hrs)	110,000 hr					
输出连接器	20PIN ATX x1, HDD/CDROM x5, FDD x2					

订购信息

型号	描述
ACE-828A-RS	280W AC-DC PS/2 ATX Power Supply

ACE-828M



规格

输入类型	90 ~ 130VAC, 180 ~ 260VAC 自动选择范围					
输出电压	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
	8A	25A (2A min)	10A (0.1A min)	0.5A	0.5A	0.72A
效率	65%					
温度	操作: -20 ~ 70°C (40 ~ 70°C 降负荷曲线) 存储: -40 ~ 75°C					
MTBF(hrs)	170,000 hr					
输出连接器	20PIN ATX x1, HDD/CDROM x5, FDD x2					

订购信息

型号	描述
ACE-828M-RS	280W AC-DC PS/2 ATX Power Supply, meets medical standard.

ACE-932A



规格

输入类型	85 ~ 130 VAC, 180 ~ 265 VAC 自动选择范围					
输出电压	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
		33A (3 A min)	8A (0.2 A min)	0.5 A	3 A	
效率	68%					
温度	操作: 0°C ~ 50°C (50°C ~ 70°C 降负荷曲线) 存储: -40°C ~ 75°C					
MTBF(hrs)	120,000 hr					
输出连接器	P8+P9 x1, Extra +5V(P10) x1, HDD/CDROM x4, FDD x2					

订购信息

型号	描述
ACE-932A-RS	300 W AC-DC PS/2 AT Power Supply

ACE-925A/AP



规格

输入类型	85 ~ 265VAC 宽范围					
输出电压	+3.3 V	+5 V	+12 V	-5 V	-12 V	+5 Vsb
		22 A (1A min)	7 A (0.1A min)	0.5 A	0.7 A	
效率	68%					
温度	0°C ~ 50°C (操作), -40°C ~ 75°C (存储)					
MTBF(hrs)	130,000 hr (ACE-925A), 140,000 hr (ACE-925AP)					
输出连接器	P8+P9 x1, HDD/CDROM x5, FDD x2					

订购信息

型号	描述
ACE-925A-RS	200 W AC-DC PS/2 AT Power Supply
ACE-925AP-RS	200 W AC-DC PS/2 AT Power Supply , with PFC

1

工业电脑
解决方案

2

视频采集
解决方案

3

嵌入式系统
解决方案

4

工业数据
采集与控制

5

平板电脑
解决方案
视觉

6

ORing
网络通讯

7

电源与外设