

ACE-A225A


1U 250 W ATX 电源支持 ErP



New



符合 80 PLUS (BRONZE)



订购信息

型号	描述
ACE-A225A-R10	250W AC-DC 1U ATX Power Supply with ErP, Meet 80 PLUS (Bronze)

尺寸

REF. ID.	PIN NO.	SIGNAL	WIRE COLOR	CABLE LENGTH
P1 / 24	1	+3.3VDC	ORANGE	500±15mm
	2	+3.3VDC	ORANGE	
	3	COM	BLACK	
	4	+5VDC	RED	
	5	COM	BLACK	
	6	+5VDC	RED	
	7	COM	BLACK	
	8	PW-OK	GRAY	
	9	+5Vsb	PURPLE	
	10	+12V2	YELLOW	
	11	+12V2	YELLOW	
	12	+3.3VDC	ORANGE	
	13	+3.3VDC	ORANGE	
	14	+3.3V sense	BROWN	
	15	-12VDC	BLUE	
	16	PS-ON	GREEN	
	17	COM	BLACK	
	18	COM	BLACK	
	19	COM	BLACK	
	20	-5V	WHITE	
	21	+5VDC	RED	
	22	+5VDC	RED	
	23	+5VDC	RED	
	24	COM	BLACK	
P2	1	COM	BLACK	500±15mm
	2	COM	BLACK	
	3	+12V1	YELLOW/BLACK	
	4	+12V1	YELLOW/BLACK	

REF. ID.	PIN NO.	SIGNAL	WIRE COLOR	CABLE LENGTH
PA	1	+12V2	YELLOW	500±15mm
	2	COM	BLACK	
	3	COM	BLACK	
	4	+5V	RED	
PB	1	+12V2	YELLOW	200±10mm
	2	COM	BLACK	
	3	COM	BLACK	
	4	+5V	RED	
PD	1	+12V2	YELLOW	200±10mm
	2	COM	BLACK	
	3	COM	BLACK	
	4	+5V	RED	
PC	1	+12V2	YELLOW	300±15mm
	2	COM	BLACK	
	3	COM	BLACK	
	4	+5V	RED	
PE	1	+5V	RED	200±10mm
	2	COM	BLACK	
	3	COM	BLACK	
	4	+12V2	YELLOW	
PF	1	+3.3VDC	ORANGE	500±15mm
	2	COM	BLACK	
	3	+5V	RED	
	4	COM	BLACK	
	5	+12V1	YELLOW/BLACK	
PG	1	+3.3VDC	ORANGE	500±15mm
	2	COM	BLACK	
	3	+5V	RED	
	4	COM	BLACK	
	5	+12V1	YELLOW/BLACK	

规格

输入	电源	90~264 VAC 宽范围		
	频率	47~63Hz		
	输入电流	4A(RMS)@115VAC2A(RMS)@230VAC		
	涌浪电流	50A 最大适用于 115VAC 100A 最大适用于 230VAC		
输出	电压	最小负载	最大负载	波纹与噪音
	+3.3V	0.3A	14.0A	50mV
	+5V	0.3A	16.0A	50mV
	+12V1	0.5A	16.0A	120mV
	+12V2	0.5A	16.0A	120mV
	-12V	0A	0.5A	120mV
	+5VSB	0A	3.0A	50mV
	-5V	0A	0.3A	100mV
	+3.3V 和 +5V 的输出总功耗不能超过 110 W. 该电源的输出总功耗是 250 W.			
过压保护	+3.3V: 3.5V-4.8V +5V: 5.5V-7V +12V1 ~+12V2: 13.4V-16V			
	短路保护 +3.3V,+5V,+12V 关闭和锁定			
	一般规格			
功率	250W			
PFC	激活			
保持时间	17 ms Min.			
效率	85%			
MTBF	100000 hr			
温度	操作: -5°C ~ 50°C 存储: -20°C ~ 80°C			
尺寸	100 x 190 x 40 (mm)			
输出连接器	20+4-pin ATX, 4-pin 12V, 4 x HDD, 2 x SATA 和 1 x FDD			

- 1 工业电脑解决方案
- 2 视频采集解决方案
- 3 嵌入式系统解决方案
- 4 工业数据采集与控制
- 5 平板电脑解决方案概览
- 6 ORing 网络通讯
- 7 电源与外设